

Date 2024/3/4  
 Condition  Carpet  Asphalt

Track Course K-Stadium(福岡県久留米市)  
 Traction High   Low

Driver Takashi Kato  
 Temperature Humidity

Track Situation  Flat  Bump

Track Size  Small  Medium  Large  X-Large

Spacer 1.0 /mm, 0 /mm, 1.0 /mm, 3.0 /mm, 4.0 /mm, 0.5 /mm, 0.5 /mm, 1.5 /mm, 0.5 /mm, Front Spring BLACK(M), Droop 0 /mm, Height Spacer 1.5 /mm, Height Spacer 0.5 /mm, Spacer 0.5 /mm

Caster 10°  
 Front Spacer 1.3 /mm, Rear Spacer 2.0 /mm  
 Camber 1.5, Toe Angle out1.5  
 Caster block 0

Lower Arm Mount WIDE  
 Kingpin Oil HQ KINGPIN OIL MEDIUM  
 Upper Arm AK12X  
 Lower Arm AK12X  
 Steering Block AL.knuckle TB20411

Upper Arm Block AK12X  
 Front Arm Support Plate No

Rear Shock 900, Length 69.7, Piston 1.2mm x 2, Spring HQ Spring Black

Ride Height 0 mm, Hole Position Bottom

Rear Shock Position 2.0 /mm, Shock Position Front Rear

Side Link, Diff Setting Solid Carbon

Side Damper MUGEN 10000

Side Spring HQ Spring S-Line LIME GREEN

Ride Height 3.6 /mm, 3.6 /mm, 3.8 /mm

Diff Setting Hard Soft

Motor 380 Size Brushless Motor 17.5T, Spur Gear 78/37, Battery G★STYLE 4500HV, Electric Speed Controller HW, Body TeamBomber LMP-KETTER (0.4 mm) 39 mm, Body Mount Position Front Rear

Transmitter SANWA M17, Receiver RX-493i, Servo SANWA PGS-HR (Type3), Servohorn XRAY, Main Chassis AK12X (Aluminum), Lower Brace AK12X (Aluminum), Back Plate TB20205 (SOFT)

Tread Front 171.5 /mm, Rear 171.5 /mm, Tire TeamBomber HQ TIRE YELLOW (M), Diameter 41.0mm, Wheel YOKOMO, Tire Treatment BLUE GRIP(CONTROL), Additive Area FL FR RL RR, Time 5分

MEMO TB20220 チタンコートキングピン, TB20230 チタンコートダンパーシャフト, TB20264S フロントサスマウントプレート (S), TB20265 アルミ製リヤホイールビス, TB20266 AK12 キャスターブロックサポート, TB20267A 3D ボディバンパー V2, TB20268 HQ フロントスプリングリテーナー, \*TB60024 リップスボイラー追加, \*バッテリー位置 全後, \*SQUARE 製タンビス使用